


Poz cija	Daudz.	Apraksts	Viena cena
	-1	<p><b>CONLIFT1</b></p>  <p><b>Uzman bu! Izstr d juma att ls var atš irties no faktisk izstr d juma izskata.</b></p> <p>Izstr d juma Nr.: 97936156</p> <p><b>Conlift1 Applications</b>          The Conlift1 is suitable for the pumping of condensate which is collected below sewer level or which cannot flow to the sewage system or drain of the building by means of a natural downward slope.</p> <p><b>Typical applications:</b></p> <ul style="list-style-type: none"> <li>• Condensate boilers. A 200 kW boiler can be drained up to 5 m duty point.</li> <li>• For condensate with a pH value above 2.5.</li> <li>• For condensate from air-conditioning systems, cooling and refrigeration systems, air dehumidifiers and evaporators.</li> <li>• For condensate with a pH value below 2.5, use Conlift2 pH+.</li> </ul> <p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Fully sealed against moisture and evaporation.</li> <li>• Quick and easy installation.</li> <li>• Very silent and smooth operation.</li> <li>• Can be mounted on the floor or on a wall.</li> <li>• Pre-assembled non-return valve.</li> <li>• Pump operation test button.</li> <li>• Incorporates high-water float switch.</li> <li>• Fully automatic operation.</li> <li>• Inlet and discharge hose connectors included.</li> </ul> <p><b>Liquid:</b>          Š idruma maksim l temperat ra: 50° °C</p> <p><b>Installation:</b></p> <p>S k a ieejas kan ls: 18-30          S k a izejas kan ls: 8-10</p> <p><b>Electrical data:</b></p> <p>Ieejas jauda - P1: 75 W          T kla frekvence: 50 Hz          Nomin lais spriegums: 1 x 230 V          Nomin l str va: 0.65 A          Korpusa klase (IEC 34-5): 24          Izol cijas klase (IEC 85): F          Kabe a garums: 1.7 m          Kabe uzga a tips: SCHUKO</p>	P c piepras juma

Poz cija	Daudz.	Apraksts	Viena cena
		<p><b>Tank:</b>            Total volume of tank(s): 2.65 l</p> <p><b>Others:</b>            Neto svars: 4.1 kg</p>	

Apraksts	V rt ba
Izstr d juma Nr.:	CONLIFT1 97936156 5710626733828
Technical:	
Maks. pl sma:	0.167 l/s
Maks. s kn. augstums:	5.5 m
Installation:	
S k a ieejas kan ls:	18-30
S k a izejas kan ls:	8-10
Liquid:	
Š idruma maksim l temperat ra:	50° °C
Min. pH:	2,7
Electrical data:	
Ieejas jauda - P1:	75 W
T kla frekvence:	50 Hz
Nomin lais spriegums:	1 x 230 V
Nomin l str va:	0.65 A
Korpasa klase (IEC 34-5):	24
Izol cijas klase (IEC 85):	F
Kabe a garums:	1.7 m
Kabe uzga a tips:	SCHUKO
Energoapg des kabelis:	H05W-F36
Tank:	
Total volume of tank(s):	2.65 l
Others:	
Neto svars:	4.1 kg

