


Poz cija	Daudz.	Apraksts	Viena cena
	-1	<p>SOLOLIFT2 WC-3</p>  <p>Uzman bu! Izstr d juma att ls var atš irties no faktisk izstr d juma izskata.</p> <p>Izstr d juma Nr.: 97775315</p> <p>Sololift2 WC-3 is a small, compact automatic lifting station suitable for pumping of wastewater off places in private dwellings where wastewater cannot be led directly to the sewer by means of a natural downward slope.</p> <p>Sololift2 WC-3 is suitable for pumping wastewater from a toilet containing toilet paper and faeces with additional connections on the lid and to the sides of the tank for e.g. washbasin, shower or bidet.</p> <p>The pumping of liquids containing other material may cause faults and limit the scope of guarantee.</p> <p>Sololift2 WC-3 is typically used to dewater:</p> <ul style="list-style-type: none"> • toilet, washbasin, shower and bidet in basements below sewer level, in connection with the renovation or modernisation of existing buildings, where the location may be remote from the main soil pipe so that a natural slope cannot be established. <p>Extremely low switching levels for lowest construction heights, advantageously in case of connection of a shower receptor.</p> <p>The compact lifting station is equipped with</p> <ul style="list-style-type: none"> - Cable with or without plug (see technical data) - Horizontal or vertical fastening possibility of discharge hose connector with several adaptors for pipes with Ø22-40mm <p>-Integrated non return valve</p> <ul style="list-style-type: none"> - Dry and high performance motor unit incl. thermal protection, pressure switch and controller - DN100 toilet connection hose - Two flexible connectors for inlet (adjustable in height) of pipes Ø36 or 40 - Slot for an alarm board with buzzer (accessory) - Manual anti clogging function and separate drain connection for service - Venting valve with overflow protection - Uplift fixation clips <p>Design according to EN12050-3 and production inspection by external institute with unique features focused on quick installation, long lasting operation and easy clean service.</p> <p>Liquid: Š idruma maksim l temperat ra: 50 °C</p>	<p>P c piepras juma</p>

Poz cija	Daudz.	Apraksts	Viena cena
		<p>Technical: Apstiprin jumi pases datu pl ksn t : CE</p> <p>Installation: S k a ieejas kan ls: 32/36/40, 36/40/50, DN 100 S k a izejas kan ls: 22/25/28/32/36/40 Pievadu skaits: 3X0,75MM2</p> <p>Electrical data: Ieejas jauda - P1: 0.62 kW T kla frekvence: 50 Hz Nomin lais spriegums: 1 x 220-240 V Nomin l str va: 3 A Cos phi - power factor: 0,92 Nomin lais trums: 2800 rpm Korpusa klase (IEC 34-5): 24 Izol cijas klase (IEC 85): F Kabe a garums: 1.2 m Kabe a tips: H05VV-F Kabe uzga a tips: TYPE F (SCHUKO)</p> <p>Others: Neto svars: 7.3 kg Bruto svars: 9.3 kg</p>	

Apraksts	V rt ba
Izstr d juma Nr.:	SOLOLIFT2 WC-3
	97775315
	5710624187241
Technical:	
Maks. s kn. augstums:	8.5 m
Apstiprin jumi pases datu pl ksn t :	CE
Installation:	
S k a ieejas kan ls:	32/36/40, 36/40/50, DN 100
S k a izejas kan ls:	22/25/28/32/36/40
Pievadu skaits:	3X0,75MM2
Liquid:	
Š idruma maksim l temperat ra:	50 °C
Electrical data:	
Ieejas jauda - P1:	0.62 kW
T kla frekvence:	50 Hz
Nomin lais spriegums:	1 x 220-240 V
Nomin l str va:	3 A
Cos phi - power factor:	0,92
Nomin lais trums:	2800 rpm
Korpasa klase (IEC 34-5):	24
Izol cijas klase (IEC 85):	F
Termisk aizsardz.:	THERMIK S06-150-05
Kabe a garums:	1.2 m
Kabe a tips:	H05VV-F
Kabe uzga a tips:	TYPE F (SCHUKO)
Others:	
Neto svars:	7.3 kg
Bruto svars:	9.3 kg
Izstr d. sortiments:	Starptautisks

