


Poz cija	Daudz.	Apraksts	Viena cena
	-1	<p>SOLOLIFT2 C-3</p>  <p>Uzman bu! Izstr d juma att ls var atš irties no faktisk izstr d juma izskata.</p> <p>Izstr d juma Nr.: 97775317</p> <p>Sololift2 C-3 is a small, compact automatic lifting station suitable for pumping of greywater (w/o faeces) off places in private dwellings where wastewater cannot be led directly to the sewer by means of a natural downward slope.</p> <p>Sololift2 C-3 is typically used for:</p> <ul style="list-style-type: none"> • cabinet showers, washbasins, bath tubs, washing machines (max. 90°C) and dishwashers in basements below sewer level or in connection with the renovation or modernisation of existing buildings, where the location may be remote from the main soil pipe so that a natural slope cannot be established. <p>Sololift2 C-3 is suitable for installation under a washbasin or particularly for confined space conditions in prewall constructions and built-in cabinets. Extremely low switching levels for lowest construction heights, advantageously in case of connection of a shower receptor.</p> <p>The compact lifting station is equipped with</p> <ul style="list-style-type: none"> - Cable with or without plug (see technical data) - Horizontal or vertical fastening possibility of discharge hose connector with several adaptors for pipes with Ø22-40mm - Integrated non return valve - Dry and high performance motor unit incl. thermal protection, level switch and controller - Flexible connectors for inlet (adjustable in height) of pipes Ø36 or 40 - Manual anti clogging function and separate drain connection for service - Venting valve with overflow protection - Uplift fixation clips <p>Design according to EN12050-2 and production inspection by external institute with unique features focused on quick installation, long lasting operation and easy clean service.</p> <p>Liquid: Š idruma maksim l temperat ra: 75 °C</p> <p>Technical: Apstiprin jumi pases datu pl ksn t : CE</p> <p>Installation: S k a ieejas kan ls: 32/36/40, 36/40/50</p>	<p>P c piepras juma</p>

Poz cija	Daudz.	Apraksts	Viena cena
		S k a izejas kan ls: 22/25/28/32/36/40 Pievadu skaits: 3X0,75MM2 Electrical data: Ieejas jauda - P1: 0.64 kW T kla frekvence: 50 Hz Nomin lais spriegums: 1 x 220-240 V Nomin l str va: 3.1 A Cos phi - power factor: 0,9 Nomin lais trums: 2800 rpm Korpusa klase (IEC 34-5): 24 Izol cijas klase (IEC 85): F Kabe a garums: 1.2 m Kabe a tips: H05VV-F Kabe uzga a tips: TYPE F (SCHUKO) Others: Neto svars: 6.53 kg Bruto svars: 8.1 kg	

Apraksts	V rt ba
Izstr d juma Nr.:	SOLOLIFT2 C-3
	97775317
	5710624187265
Technical:	
Maks. s kn. augstums:	8.5 m
Apstiprin jumi pases datu pl ksn t :	CE
Installation:	
S k a ieejas kan ls:	32/36/40, 36/40/50
S k a izejas kan ls:	22/25/28/32/36/40
Pievadu skaits:	3X0,75MM2
Liquid:	
Š idruma maksim l temperat ra:	75 °C
Electrical data:	
Ieejas jauda - P1:	0.64 kW
T kla frekvence:	50 Hz
Nomin lais spriegums:	1 x 220-240 V
Nomin l str va:	3.1 A
Cos phi - power factor:	0,9
Nomin lais trums:	2800 rpm
Korpasa klase (IEC 34-5):	24
Izol cijas klase (IEC 85):	F
Termisk aizsardz.:	THERMIK S06-140-05
Kabe a garums:	1.2 m
Kabe a tips:	H05VV-F
Kabe uzgaa tips:	TYPE F (SCHUKO)
Others:	
Neto svars:	6.53 kg
Bruto svars:	8.1 kg
Izstr d. sortiments:	Starptautisks

