


Poz cija	Daudz.	Apraksts	Viena cena
	-1	<p>SOLOLIFT2 D-2</p>  <p>Uzman bu! Izstr d juma att ls var atš irties no faktisk izstr d juma izskata.</p> <p>Izstr d juma Nr.: 97775318</p> <p>Sololift2 D-2 is a small, compact automatic lifting station suitable for pumping of wastewater off places in private dwellings where greywater (w/o faeces) cannot be led directly to the sewer by means of a natural downward slope.</p> <p>Sololift2 D-2 is typically used for:</p> <ul style="list-style-type: none"> • cabinet showers, washbasins or bidets in basements below sewer level, in connection with the renovation or modernisation of existing buildings, where the location may be remote from the main soil pipe so that a natural slope cannot be established. <p>Extremely low switching levels for lowest construction heights, advantageously in case of connection of a shower receptor.</p> <p>Sololift2 D-2 is suitable for confined space conditions in built-in cabinets or also below shower receptors or pedestals.</p> <p>The pumping of liquids containing other material may cause faults and limit the scope of our guarantee.</p> <p>The compact lifting station is equipped with</p> <ul style="list-style-type: none"> - Cable with or without plug (see technical data) - Discharge hose connector with several adaptors for pipes with Ø22-36mm <p>-Integrated non return valve</p> <ul style="list-style-type: none"> - Dry and high performance motor unit incl. thermal protection, pressure switch and controller - Flexible connectors for inlet (adjustable in height) of pipes Ø36 or 40 - Manual anti clogging function and separate drain connection for service - Venting valve with overflow protection - Uplift fixation clips <p>Design according to EN12050-2 and production inspection by external institute with unique features focused on quick installation, long lasting operation and easy clean service.</p> <p>Liquid: Š idruma maksim l temperat ra: 50 °C</p> <p>Technical: Apstiprin jumi pases datu pl ksn t : CE</p>	<p>P c piepras juma</p>

Poz cija	Daudz.	Apraksts	Viena cena
		<p>Installation:</p> <p>S k a ieejas kan ls: 36/40/50</p> <p>S k a izejas kan ls: 22/32</p> <p>Pievadu skaits: 3X0,75MM2</p> <p>Electrical data:</p> <p>Ieejas jauda - P1: 0.28 kW</p> <p>T kla frekvence: 50 Hz</p> <p>Nomin lais spriegums: 1 x 220-240 V</p> <p>Nomin l str va: 1.3 A</p> <p>Cos phi - power factor: 0,95</p> <p>Nomin lais trums: 2800 rpm</p> <p>Korpasa klase (IEC 34-5): 24</p> <p>Izol cijas klase (IEC 85): F</p> <p>Kabe a garums: 1.2 m</p> <p>Kabe a tips: H05VV-F</p> <p>Kabe uzga a tips: TYPE F (SCHUKO)</p> <p>Others:</p> <p>Neto svars: 4.21 kg</p> <p>Bruto svars: 5 kg</p>	

Apraksts	V rt ba
Izstr d juma Nr.:	SOLOLIFT2 D-2 97775318 5710624187272
Technical:	
Maks. s kn. augstums:	5.5 m
Apstiprin jumi pases datu pl ksn t :	CE
Installation:	
S k a ieejas kan ls:	36/40/50
S k a izejas kan ls:	22/32
Pievadu skaits:	3X0,75MM2
Liquid:	
Š idruma maksim l temperat ra:	50 °C
Electrical data:	
Ieejas jauda - P1:	0.28 kW
T kla frekvence:	50 Hz
Nomin lais spriegums:	1 x 220-240 V
Nomin l str va:	1.3 A
Cos phi - power factor:	0,95
Nomin lais trums:	2800 rpm
Korpasa klase (IEC 34-5):	24
Izol cijas klase (IEC 85):	F
Termisk aizsardz.:	THERMIK S06-160-05
Kabe a garums:	1.2 m
Kabe a tips:	H05VV-F
Kabe uzga a tips:	TYPE F (SCHUKO)
Others:	
Neto svars:	4.21 kg
Bruto svars:	5 kg
Izstr d. sortiments:	Starptautisks

