

O'Pro Central Domestic

ROBUST CENTRAL DOMESTIC WATER HEATER EQUIPPED WITH O'PRO PROTECTION



+ PRODUCT

COMFORT

- Large variety of sizes to meet all installation requirements
- Vertical and horizontal wall-mounted & floor-standing models available
- Large tank capacity for more hot water

QUALITY - DURABILITY





- Long tank lifetime thanks to O'Pro exclusive anti-corrosive system to permanently combat rust
- Magnesium anode for strengthened tank protection
- New generation diamond-quality enamel (glass-lined inner tank)
- Pressure relief valve
- Dielectric union
- Specific lip gasket to prevent corrosion around flange

USER-FRIENDLINESS

- IP 24 - full compliance with European standards for electrical safety and user protection
- Heating light indicator

SAVINGS

- Mechanical thermostat with integrated security
- High-efficiency water inlet
- CFC-free high-density insulation for more energy savings

ELECTRIC WATER HEATER		150 TO 200 L (VERTICAL AND HORIZONTAL WALL-MOUNTED)	200 TO 500 L (FLOOR-STANDING)
 <p>Model available*</p>	 <p>Temperature regulation</p>	 <p>Anti-corrosive technology</p>	 <p>Copper heating element</p>

*Model types: A: Vertical wall-mounted / B: Horizontal wall-mounted / C: Floor-standing

O'Pro Central Domestic

INSTALLATION DIMENSIONS

Vertical wall-mounted

Floor-standing

Horizontal wall-mounted

- 1 Diamond-quality enamel (glass-lined tank)
- 2 Optimised stainless outlet pipe
- 3 Magnesium anode
- 4 Sheathed immersion heating element
- 5 Inlet diffuser
- 6 O'Pro anti-corrosive system
- 7 High-density polyurethane foam 0% CFC
- 8 Dielectric union
- 9 Thermostat

TECHNICAL DATA

CAPACITY (L)	OUTPUT (W)	VOLTAGE (V)	ENERGY CONSUMPTION (kWh/24 h AT 65°C)	HEAT-UP TIME AT 60°C (ΔT=50°C)	HOT WATER CAPACITY AT 40°C (L)	COOLING CONSTANT
O'Pro Central Domestic Vertical wall-mounted						
150	2200	230 (220/240)	1.65	4h10	239	-
200	2200	230 (220/240)	2.04	5h33	376	-
O'Pro Central Domestic Horizontal wall-mounted						
150	1650	230 single phase	1.75	5h29	277	0.25
200	2200	230 single phase	2.07	5h33	371	0.22
O'Pro Central Domestic Floor-standing						
200	2200	230 single phase	1.75	4h59	354	0.20
250	3000	230 single phase	2.22	4h46	465	0.19
300	3000	230 single phase	2.49	5h38	531	0.18
500	5000	400 3-phase88	2.60	5h53	Criteria measured on tanks ≤ 300L	0.11

DIMENSIONS

CAPACITY (L)	DIMENSIONS (mm)									FLANGE OPENING (Ø) mm	NET WEIGHT (Kg)	ERP ENERGY CLASS	PROFILE
	Ø	A	B	C	D	E	F	H	Z				
O'Pro Central Domestic Vertical wall-mounted													
150	-	1240	505	800	520	175	440	-	-	72	41	C	M
200	-	1570	505	800	525	175	440	-	-	72	42	C	L
O'Pro Central Domestic Horizontal wall-mounted													
150	530	-	800	-	-	-	-	1140	150	72	39	C	L
200	530	-	800	-	-	-	-	1460	470	72	48	C	L
O'Pro Central Domestic Floor-standing													
200	530	300	600	-	-	-	-	1485	-	-	43	C	M
250	530	300	600	-	-	-	-	1805	-	-	57	C	L
300	570	300	640	-	-	-	-	1765	-	-	65	C	L
500	750	310	850	-	-	-	-	1840	-	-	154	C	L