

Daudzums | **Apraksts**

1

COMFORT 15-14 BA PM



Piez me. Produkta att Is var atš irties no faktisk produkta izskata.

Produkta Nr.: [97916757](#)

The Grundfos Comfort BA PM and BXA PM pumps are designed for recirculation of domestic hot water in single- and two-family houses securing hot water instantly to all faucets. The pumps have a corrosion-resistant pump housing suitable for drinking water and are powered by a single-phase, high-efficiency ECM with permanent-magnet rotor.

The AUTOADAPT function incorporates an event log that learns the scheme of demand for hot water in the domestic hot-water system. Via the event log, the pump predicts when to start circulating hot water ensuring hot water is instantly available at all use points. Should the consumption pattern change, for example during holidays, the pump will recognise the standstill after 24 hours and automatically adapts to holiday mode. When returning from holiday, the pump will automatically resume the same consumption pattern as before the holiday.

The unique AUTOADAPT feature is saving up to 48 % heat energy and 97 % motor energy compared with a standard pump in continuous operation. Additionally, the pump can be set to temperature control mode and continuous operation 100 % for commissioning of the pump or 24 hours instant hot water.

The pumps are equipped with a flushing and disinfection function which automatically circulates water to protect against bacterial growth in the pipes.

COMFORT BXA PM has a built-in isolating valve and a non-return valve (fitting). This ensures that maintenance can be carried out without draining the system. The non-return valve also prevents reversed flow during operation.

Š idrums:

S kn jamais š idrums: dens

Š idruma temperat ras diapazons: 2 .. 95 °C

izv l t š idruma temperat ra: 60 °C

Bl vums pie izv l t s š idruma temperat ras: 983.2 kg/m³

Tehn.:

TF klase: 95

Apstiprin jumi pases datu pl ksn t : CE,VDE,EAC,WEEE

Materi li:

S k a korpuss: Brass

Darbrats: Kompoz ts

Uzst d šana:

Maksim lais darba spiediens: 10 b ri

Type of connection: Rp

Cauru u savienojums: 1/2

Garums no viena pievienojuma l dz otram: 80 mm

Elektriskie dati:

Maks. pat r jam jauda: 7 W

T kla frekvence: 50 Hz

Nomin lais spriegums: 1 x 230 V

3. truma str va: 0.07 A

Kondensatora lielums - darb ba: 0.6 µF

Korpusa klase (IEC 34-5): IP44

Daudzums	Apraksts
----------	----------

Izol cijas klase (IEC 85):	F
Citi:	
Neto svars:	0.98 kg
Bruto svars:	1.08 kg
Pieg des apjoms:	0.003 m ³
Danish VVS No.:	380634014
Swedish RSK No.:	5803088
Norwegian NRF no.:	9042115
Izcelsmes valsts:	DE
Muitas tarifa Nr.:	84137030

Apraksts	Vērtība
Vispārīgā informācija:	
Produkta nosaukums:	COMFORT 15-14 BA PM
Produkta Nr.:	97916757
EAN numurs:	5710626363506
Cena:	EUR 288.1
Tehniskie dati:	
Trūkst Nr.:	1
Maksimālais spiedienaugstums:	14 dm
TF klase:	95
Apstiprinājumi pasēs datu plūsmām:	CE,VDE,EAC,WEEE
Materiāli:	
Skaņķermeņa materiāls:	Brass
Darbrāts:	Kompozīts
Uzstādīšana:	
Maksimālais darba spiediens:	10 bari
Type of connection:	Rp
Cauru savienojums:	1/2
Garums no viena pievienojuma līdz otram:	80 mm
Šķidrums:	
Skaņķermeņa šķidrums:	dens
Šķidruma temperatūras diapazons:	2 .. 95 °C
Izvēlētā šķidruma temperatūra:	60 °C
Blīvums pie izvēlētās šķidruma temperatūras:	983.2 kg/m³
Elektriskie dati:	
Maksimālā jauda:	7 W
Tīkla frekvence:	50 Hz
Nominālais spriegums:	1 x 230 V
Strāva:	0.07 A
Kondensatora lielums - darbība:	0.6 µF
Korpuse klase (IEC 34-5):	IP44
Izolācijas klase (IEC 85):	F
Motora aizsardzība:	ELECT.
Termiskā aizsardzība:	Aizsardzība pēc tinumu pretestības
Citi:	
Neto svars:	0.98 kg
Bruto svars:	1.08 kg
Piegādes apjoms:	0.003 m³
Danish VVS No.:	380634014
Swedish RSK No.:	5803088
Norwegian NRF no.:	9042115
Izcelsmes valsts:	DE
Muitas tarifa Nr.:	84137030

