

Daudzums	Apraksts
1	MAGNA1 40-150 F  Piezīme. Produkta attēls var atšķirties no faktiskā produkta izskata. Produkta Nr.: 99221306 The new MAGNA1 is the simple option for a job well done. It is the perfect choice when replacing older circulators and due to its compliance with the EuP 2015 regulations, substantial savings on electricity is a reality. The ideal choice for basic performance needs in applications where basic system control and monitoring is desired. • Monitoring via the fault relay, ensuring peace of mind • Digital start/stop input available for remote pump control • Continuous operation and reduced downtime with the wireless twin pump function (available on twin-head pumps) • High energy efficiency resulting in substantial savings on electricity • Easy setup and operation via the simple user interface • No maintenance due to the canned-rotor type design. MAGNA1 is the simple and efficient choice for most applications including • Heating - Main pump - Mixing loops - Heating surfaces • Cooling - Air conditioning surfaces - Ground source heat pump systems - Smaller chiller applications Šķidrums: Sūkņējamais šķidrums: Ūdens Šķidruma temperatūras diapazons: -10 .. 110 °C Izvēlēta šķidruma temperatūra: 60 °C Blīvums pie izvēlētas šķidruma temperatūras: 983.2 kg/m³ Tehn.: TF klase: 110 Apstiprinājumi pasēs datu plāksnītē: CE,VDE,EAC,CN ROHS,WEEE Materiāli: Sūkņa korpusa: Čuguns EN-GJL-250 ASTM A48-250B Darbrats: PES 30 %GF Uzstādīšana: Apkārtējās vides temperatūras diapazons: 0 .. 40 °C Maksimālais darba spiediens: 10 bāri Standarta atloks: DIN Cauruļu savienojums: DN 40 Spiediena pakāpe: PN6/10 Garums no viena pievienojuma līdz otram: 250 mm Elektriskie dati: Ieejas jauda - P1: 16.01 .. 615 W Tīkla frekvence: 50 Hz Nominālais spriegums: 1 x 230 V Maksimālais strāvas patēriņš: 0.18 .. 2.71 A Korpusa klase (IEC 34-5): X4D Izolācijas klase (IEC 85): F Citi:



Uzņēmuma nosaukums: Akvedukts, SIA
Izveidoja: Guntis Valainis
Tālrunis: 67606390
E-pasts: guntis@akvedukts.lv
Datums: 16.08.2019

Daudzums	Apraksts
	Enerģija (EEI): 0.20 Neto svars: 16.3 kg Bruto svars: 17.6 kg Piegādes apjoms: 0.039 m³ Finnish LVI No.: 4615191

