




Pozīcija	Daudz.	Apraksts	Viena cena
	1	<p>CONLIFT1</p>  <p>Uzmanību! Izstrādājuma attēls var atšķirties no faktiskā izstrādājuma izskata.</p> <p>Izstrādājuma Nr.: 97936156</p> <p>Conlift1 Applications The Conlift1 is suitable for the pumping of condensate which is collected below sewer level or which cannot flow to the sewage system or drain of the building by means of a natural downward slope. Typical applications: • Condensate boilers. • For condensate with a pH value above 2.5. • For condensate from air-conditioning systems, cooling and refrigeration systems, air dehumidifiers and evaporators. • For condensate with a pH value below 2.5, use Conlift2 pH+.</p> <p>Features</p> <ul style="list-style-type: none"> • Fully sealed against moisture and evaporation. • Quick and easy installation. • Very silent and smooth operation. • Can be mounted on the floor or on a wall. • Pre-assembled non-return valve. • Pump operation test button. • Incorporates high-water float switch. • Fully automatic operation. • Inlet and discharge hose connectors included. <p>Šķidrums: Šķidruma maksimālā temperatūra: 50° °C Liquid temp: 20 °C Blīvums: 998.2 kg/m³</p> <p>Technical: Līknes pielāgšana: ISO 9906:2012 Grade 3B</p> <p>Uzstādīšana: Sūkņa ieejas kanāls: 18-30 Sūkņa izejas kanāls: 8-10</p> <p>Elektriskie dati: Ieejas jauda - P1: 75 W Tīkla frekvence: 50 Hz Nominālais spriegums: 1 x 230 V Nominālā strāva: 0.65 A Korpusa klase (IEC 34-5): IP24 Izolācijas klase (IEC 85): F Kabeļa garums: 1.7 m</p>	

GRUNDFOS®

Uzņēmuma nosaukums: Akvedukts Sia
Izveidotājs: Guntis Valainis
Tālrunis: 67805318, 67606390
Fakss: 67408118
Datums: 24.03.2017.

Pozīcija	Daudz.	Apraksts	Viena cena
		Kabeļuzgaļa tips: SCHUKO Tvertne: Kopējais tvertnes(-u) tilpums: 2,65 l Citi: Neto svars: 4.1 kg	

Apraksts	Vērtība
Izstrādājuma nosaukums:	CONLIFT1
Izstrādājuma Nr.:	97936156
EAN numurs:	5710626733828
Technical:	
Maks. plūsma:	0.6 m ³ /st
Maks. sūkn. augstums:	5.5 m
Līknes pielaišana:	ISO 9906:2012 Grade 3B
Uzstādīšana:	
Sūkņa ieejas kanāls:	18-30
Sūkņa izejas kanāls:	8-10
Šķidrums:	
Šķidruma maksimālā temperatūra:	50 °C
Liquid temp:	20 °C
Blīvums:	998.2 kg/m ³
Min. pH:	2,7
Elektriskie dati:	
Ieejas jauda - P1:	75 W
Tīkla frekvence:	50 Hz
Nominālais spriegums:	1 x 230 V
Nominālā strāva:	0.65 A
Korpusa klase (IEC 34-5):	IP24
Izolācijas klase (IEC 85):	F
Kabeļa garums:	1.7 m
Kabeļuzgaļa tips:	SCHUKO
Energoapgādes kabelis:	H05W-F36
Tvertne:	
Kopējais tvertnes(-u) tilpums:	2,65 l
Citi:	
Neto svars:	4.1 kg

