


Poz cija	Daudz.	Apraksts
	1	<p>UPA15-120 AUTO</p>  <p>Uzman bu! Izstr d juma att ls var atš irties no faktisk izstr d juma izskata.</p> <p>Izstr d juma Nr.: 98699677</p> <p>Applications</p> <ul style="list-style-type: none"> • Domestic applications requiring high pressure in taps, showers, gas boiler inlets and other domestic tapping points: • Roof top tank boosting • Instant (tank-less) boiler boosting • Domestic boosting with inlet pressure <ul style="list-style-type: none"> • Suitable for hot and cold water applications. Temperatures up to 95° C. <ul style="list-style-type: none"> • Capable of boosting water in multiple outlets at a time (1-4 taps) making it suitable for flats with a shared water supply and for one-family houses: • Urban areas with low water pressure at peak demand • Flats sharing low-pressure water supply • Rural areas with low water pressure <p>Features and benefits</p> <p>New built-in flow switch The new unique and patented built-in flow switch automatically starts the pump when a tapping point is turned on, thereby increasing the water pressure. When the tap is closed, the flow switch immediately stops the pump.</p> <p>Compact design The compact design makes the UPA 120 perfect for installation even in confined spaces.</p> <p>Automatic start/stop The built-in flow switch automatically starts and stops the pump according to demand to ensure the required water pressure.</p> <p>Easy to install The UPA 120 with the new built-in flow switch is very easy to install. It is virtually a plug-and-pump solution.</p> <p>Silent operation Built on the high-quality wet-runner technology the UPA 120 offers smooth and silent operation, making it a popular choice in private homes.</p> <p>Š idrums:</p> <p>S kn jamais š idrums: dens</p> <p>Š idruma temperat ras diapazons: 2 .. 95 °C</p> <p>Liquid temp: 60 °C</p> <p>Bl vums: 983.2 kg/m³</p> <p>Technical:</p> <p>TF klase: 95</p> <p>Apstiprin jumi pases datu pl ksn t : CE</p>

Poz cija	Daudz.	Apraksts
		<p>Materi li: S k a korpuss: uguns S k rats: PP Composit</p> <p>Uzst d šana: Maks. darba spiediens: 10 bar Pievienojums: 1 Garums no viena pievienojuma l dz otram: 200 mm</p> <p>Elektriskie dati: C darb ba: 6 μF Maks. pat r jam jauda: 200 W T kla frekvence: 50 Hz Nomin lais spriegums: 1 x 230 V 3 truma str va: 0.89 A Kondensatora lielums - darb ba: 6 μF Korpusa klase (IEC 34-5): X2D Izol cijas klase (IEC 85): F</p> <p>Citi: Bruto svars: 5 kg Pieg des tilpums: 0.006 m³</p>

Apraksts	Vērtība
Vispārīgā informācija:	
Izstrādājuma nosaukums:	UPA15-120 AUTO
Izstrādājuma Nr.:	98699677
EAN numurs:	5712600117617
Cena:	Pēc pieprasījuma
Technical:	
Modela Nr.:	1
Maksimālā cauruma augstums:	120 dm
TF klase:	95
Apstiprinājumi pasēs datu plūsmām:	CE
Materiāli:	
Sūkņa korpusa:	Alumīnijs
Sūkņa rats:	PP Composit
Uzstādīšana:	
Maksimālā darba spiediens:	10 bar
Pievienojums:	1
Garums no viena pievienojuma līdz otram:	200 mm
Šķidrums:	
Sūkņa jāmācītais šķidrums:	dens
Šķidruma temperatūras diapazons:	2 .. 95 °C
Liquid temp:	60 °C
Blīvums:	983.2 kg/m ³
Elektriskie dati:	
Capacitance:	6 μF
Maksimālā patēriņa jauda:	200 W
Testa frekvence:	50 Hz
Nominālā sprieguma:	1 x 230 V
3 fāzu strāva:	0.89 A
Kondensatora lielums - darbība:	6 μF
Korpusa klase (IEC 34-5):	X2D
Izolācijas klase (IEC 85):	F
Motora aizsardzība:	Kontakti
Termiskā aizsardzība:	iekšējā
Citi:	
Bruto svars:	5 kg
Pieņēšanas tilpums:	0.006 m ³
Valsts kods:	EU

