

Curaflex Nova® Senso

against pressing water or non-pressing water

- sealing system for penetrations
- to install in **preinstalled pipe sleeve** or **core bore in waterproof concrete** (white tank)
- suitable **for flexible pipes**



Product benefits

- with ITL system for optimal contact pressure – installation without special tool
- with **STS** for caring sealing, therefore ideal for flexible pre-insulated plastic pipes and flexible cable protection pipes
- simple installation due to precise dimensions
- permanently sealed without re-tensioning (maintenance-free)
- high sealing capability in terms of the gasket insert due to **DPS** and **DOYMA-Grip**

25
Years
Guarantee

Technical details

- gas-tight
- accepts angular deviations of service duct up to 8°
- 45 mm seal width
- NB 150 for pipes with ext. dia. 75, 90 mm
- NB 200 for pipes with ext. dia. 110, 125, 140, 160 mm

The gasket insert consists of:

- blue frame rings made out of high-performance plastic, elastomer and seal rings, 45 mm wide, made out of EPDM (**DOYMA-Grip**) with **DPS**
- **DDE (DOYMA Diameter Extension)** modules in black and orange
- **ITL (Integrated Torque Limiter)** nuts
- **STS (Soft Tight System)**: for caring sealing
- screws made of stainless steel

Accessories from page 88

pipe external diameter from - to	NB pipe sleeve/ core bore [mm]
74 - 76	150 (149 - 153)
89 - 91	
109 - 111	
109 - 111	200 (199 - 203)
124 - 126	
139 - 141	
159 - 161	
L _D (max. overall length) [mm]: 105	

